



1. SERVICE LINE STUB MUST EXTEND TO THE PROPERTY LINE. A DISCONNECT CLEANOUT SHALL BE INSTALLED ON THE PUBLIC SIDE AT THE PROPERTY LINE. THE DISCONNECT CLEANOUT TEE FOR ALL 4" SERVICE LINES SHALL BE THE DISCONNECT CLEANOUT HOUSING AS MANUFACTURED BY ELDER VALVE, INC.
2. INTEGRAL WYE FITTINGS ON THE SEWER MAIN ARE TO BE USED FOR THE CONNECTION OF THE SERVICE LINE TO THE SEWER MAIN. FOR IN-SERVICE MAINS, USE THE DISTRICT'S CUT-IN SERVICE WYE DETAIL.
3. THE DEPTH OF THE SEWER LINE AT THE PROPERTY LINE SHALL NOT BE LESS THAN 3.75 FEET, NOR MORE THAN 7 FT AS MEASURED FROM THE TOP OF THE PIPE TO THE SURROUNDING GRADE UNLESS THE DISTANCE TO THE BUILDING REQUIRES GREATER DEPTH.
4. BEDDING FROM BOTTOM OF THE SERVICE LINE TO 12" OVER THE TOP OF PIPE SHALL BE 3/8" WASHED ROCK CHIPS.

DETAIL NO.
SM440

STANDARD DETAIL

SEWER BUILDING CONNECTION

SUPERSTITION MOUNTAINS
COMMUNITY FACILITIES DISTRICT
NO. 1



DETAIL NO.
SM440